

performance / healthcare in-stock



om



om

	Pattern/ Width	Content and Backing	Finish	Weight/ Linear Yd.	Pattern Repeat	Directional	Abrasion (Wyzenbeek)	Breaking Strength	Crocking	Light Fastness	Cleaning Code
Cinema	54"	100% Polyurethane Backing: 70% Polyester; 30% Cotton	Antimicrobial	20.3 oz. lin. yd.	none	no	200,000 double rubs	warp: 130 lbs. wet: 120 lbs.	dry: class 5 wet: class 5	200 hours	WS, BC:5:1 water/bleach
Illusion	54"	Vinyl Backing: 100% Polyester, Mellohide™	MorClean™ FR free	30 +/- 2 oz. per lin. yd.	none	no	200,000 double rubs	warp: 108 min. fill: 71 lbs. min	dry: good wet: good	200 hours	WS, BC: 9:1 water/bleach
Stage	54"	70% Vinyl, 30% Polyester Backing: 100% Polyester	Permablock	30 oz. lin. yd.	none	yes	930,000 double rubs	warp: 121 lbs. fill: 72 lbs	dry: class 4 min	1000 hours	WS, BC: 9:1 water/bleach
Hopsack	54"	Vinyl Backing: Polyester	Advanced Soil and Stain Resistant Top Coat	30.0 oz./ lin. yd. +/- 1.0 oz.	none	directional	100,000+ double rubs	warp: 121 lbs. min fill: 72 lbs. min	dry: excellent wet: excellent	1000 hours class 4.5	WS, BC: 4:1 water/bleach
Cover Cloth	54"	56% Repreve® Post Consumer Recylced Polyester, 44% Polyester	Crypton Green®	0.88 lbs. lin. yd.	none	yes	200,000 double rubs	warp: 121 lbs. fill: 72 lbs.	dry: excellent wet: excellent	1000 hours	W, BC 10:1 water/bleach

Flammability: All fabrics passes California Technical Bulletin 117-2013, Section 1; UFAC Class 1; NFPA 260 Class 1

* This term and any corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Multiple factors affect fabric durability and appearance retention, including end-use application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.

Cleaning Information: W, WS – Water Solvent: Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC - Bleach Cleanable: Follow bleach to water dilution ratio. Do not clean/disinfect fabric for longer than 10 minutes using diluted bleach solution. Always ricse promptly with clean water after applying the bleach solution.

Additional Notes:

Individual samples available. Please send requests to samples @omseating.com Manufacturers will always attempt to ship to a satisfactory commercial match. Because of industry standard dye lot variation, colors may not match exactly. Specifications are correct at time of printing and are subject to change without notification. Additional specifications may be available by contacting OM.

Visit www.omseating.com for more information about ergonomics and the design of omseating.

omseating 1110 south mildred avenue, ontario, california 91761 | www.omseating.com | 877.776.5678 | fax 909.392.4567

performance / healthcare in-stock

	omseating
--	-----------

om performance / healthcare in-stock

					_
cinema – PVC free	academy 3P31	ensemble 3P32	cue 3P36	icon 3P33	hopsack – vinyl
blockbuster 3P34	noir 3P30	thriller 3P37	cameo 3P38	casablanca 3P40	cori 4V14
illusion — vinyl					cover cloth - Crypton®
	teller 3V81	houdini 3V80	siegfried 3V88	roy 3V85	
penn 3V84	copperfield 3V86	angel 3V89	blaine 3V83	burton 3V87	indigo 4C04
stage – vinyl	cats 3V50	grease 3V53	hamilton 3V56	chicago 3V52	

cinder 4V10



fjord 4V15



platinum 4C02



oat 4C06

aida 3V55

frozen 3V54

shrek 3V58

pł

fame 3V59

phantom 3V57



om performance / healthcare in-stock



mystic 4V19



hemlock 4V18



vesper 4C05



sorrel 4C08



ahoy 4V13



grass 4V12



gunmetal 4C01



syracuse 4C03



twine 4V16



koi 4V17



jet 4C00



russet 4C07