om o

crush collection in-stock

om 📗 (

crush collection in-stock

beau

bodd					
Content:	70% Polypropylene, 30% Polyester	PERFORMANCE Surface Abrasion:	TEST METHOD ASTM D-4157 (Wyzenbeek)	RESULTS Exceeds 100,000 Double Rubs	
Width:	54"	Breaking Strength:	ASTM D-5034	Warp: 214 lbs / Fill: 450 lbs	
Weight:	16.04 oz./linear yard	Seam Slippage:	ASTM D-4034	Warp: 50 lbs / Fill: 80 lbs	
Backing:	Latex	Colorfastness to Crocking:		Dry: Class 4 / Wet: Class 4	
Finish:	Stain Repellent	Colorfastness to Light:	AATCC 16.3 Option 3	40 hrs Grade 5	
Repeat:	None				
Directional:	Yes				
Railroaded:	No	Reduced Environmental Impact: GREENGUARD Gold Certified			
Flammability* Passes Cal 117-2013; NFPA 260/UFAC Class 1; May comply with Cal. Tech. Bul. 133 when combined with appropriate components.		Cleaning Code: Cleaning Instructions:	W (Water-Based Cleaner) Spot clean, using the foam only from a water-based cleaning agent, su as a mild detergent or non-solvent upholstery shampoo product. Apply foam with a soft brush in a circular motion. Always rinse promptly with clean water. Pretest small area before proceeding.		

Cleaning Code: Cleaning Instructions:

BC (Bleach Cleanable)

- 1 part bleach, 9 parts water = 10% bleach, 90% water solution
 Do not clean/disinfect fabric for longer than 10 minutes using the 10% bleach solution.
- Always rinse promptly with clean water after applying the bleach solution.
- Failure to do so will void any and all warranties.

bliss

Width: 54" Weight: 0.86 oz./linear yard Backing: Acrylic Finish: None Repeat 3.75" vertical / 7.5" horizontal Directional: Yes Railroaded: No		Surface Abrasion: Breaking Strength: Seam Slippage: Colorfastness to Crocking:	ASTM-D-4157 (Wyzenbeek) ASTM-D-5034 ASTM-D-4034 AATCC 8	170,000 Double Rubs Warp: 50 lbs / Fill: 50.0 lbs. Warp: 25.0 lbs / Fill: 25.0 lbs. Dry: Class 4 min / Wet: Class 3 min
		Colorfastness to Light: AATCC 16.3 Option 3 40 hours - Grade 5 min Reduced Environmental Impact: Recycled Fiber Content; GREENGUARD Gold Certified; SF 336 Compliant		
Flammability* California TB Bu UFAC Class 1 NFPA 260 Class	Passes	Cleaning Code: Cleaning Instructions:	W (Water Based Foam or Cleaner) Clean with water based foam or cleaner Do not saturate with liquids Do not get the furniture wet Do not use dry cleaning solvents	

XOX

Content: Width: Weight: Backing: Finish: Repeat: Directional: Railroaded:	100% Polyester 54" 17.27 oz./linear yard Acrylic Stain Repellent-PFOA & PFOS free 4.8" vertical / 4.8" horizontal Yes No	PERFORMANCE Surface Abrasion: Breaking Strength: Seam Slippage: Colorfastness to Crocking: Colorfastness to Light:	TEST METHOD ASTM D-4157 (Wyzenbeek) ASTM-D-5034 ASTM-D-4034 AATCC 8 AATCC-16.3 Option 3	RESULTS Passes 80,000 Double Rubs Warp: 246 lbs. / Fill: 282 lbs. Warp: 96 lbs. / Fill: 84 lbs. Dry: Class 4 min / Wet: Class 4 40 hours - Grade 5
Flammability* Passes Cal 117-2013; NFPA 260/UFAC Class 1; May comply with Cal. Tech. Bul. 133 when combined with appropriate components		Cleaning Code: Cleaning Instructions:	S (Solvent Cleaner) Spot clean, using a mild water-free solvent or dry cleaning product Avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.	

Additional Notes: Individual samples available. Manufacturers will always attempt to ship to a satisfactory commercial match. Because of industry standard dye lot variation, colors may not match exactly. Specifications are correct at time of printing and are subject to change without notification. Additional specifications may be available by contacting OM.

*This term and any corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

 $\label{thm:composition} \mbox{Visit www.} \mbox{\bf om} \mbox{seating.com for more information about ergonomics and the design of } \mbox{\bf om} \mbox{seating.}$

omseating

omseating 1110 south mildred avenue, ontario, california 91761 | www.omseating.com | 877.776.5678 | fax 909.392.4567

crush collection in-stock

crush collection in-stock





